


T 6 S R. 10 W R.D. HEBO County TILLAMOOK J-5\*  
 Merid. WILL. N.F. SIU SLAW State ORE. **USFS FILE**

CORNER DIAGRAM  


DESCRIBE CORNER MONUMENT FOUND GLO 1890 SET POST & MK  
 6" SPRUCE, N. 80 1/2° W., 26 LKS. **# 986**  
 6" SPRUCE, S. 32° W., 16 LKS.  
 6" ~~SPRUCE~~ ALDER, S. 86° E., 13 LKS.  
 10" SPRUCE, S. 13° E., 47 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND  
 FOUND 27" DEAD FIR, S. 32° W., 10 1/2 FT. WITH ~~QAD~~  
 CHOPPED OPEN FACE. TWO SCRIBE MARKS  
 BE SEEN ON ROTTED FACE. **CAN**  
 FOUND 48" FIR, S. 13° E., 31 FT. WITH CRUISE  
**MARK & AND VISIBLE HEALED WITNESS FACE**

PHOTO IDENTIFICATION DATA  
 Photo No. ETT-5-159  
 Filed At. HEBO  
 Object Ident. WITHIN 5 FT.  
 Ident. By L. WHITMORE  
*Signature*

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER  
 THE NW BT IS A SMALL ROTTED LOG LYING  
 UPON  
 THE GROUND.  
 THE S. E. ALDER IS GONE.  
 ALL BT'S ARE FIR NOT SPRUCE IN ORIGINAL.

PLANE COORDINATE POSITION DATA  
 State \_\_\_\_\_ Zone \_\_\_\_\_

COPIES SENT TO SO \_\_\_\_\_  
 Estab. By \_\_\_\_\_ Agency \_\_\_\_\_

NOTES

*Leonard Whitmore Forestry Tech Hebo 2-8-73*

MONUMENT DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT  
**SET 1/2" IRON ROD.**

*Leonard Whitmore is the Deputy County Surveyor empowered in re-witness  
 positive identifiable found monuments in connection with his work  
 will USFS J.L. Conlin 12/74 "T6SR10WS8CSB"*

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING  
**I SCRIBE A 37" FIR, N. 11° E., 28 FT. SCRIBED "T6SR10WS8" VAR. 21° DISTANCES TO SIDE CENTER.**

*Leonard Whitmore, Tillamook County Deputy Surveyor, 2-8-73*

Work Done By \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_ State Registration No. \_\_\_\_\_  
 or Agency \_\_\_\_\_

Certified Cor. Record Prepared? Yes No Filed At \_\_\_\_\_ Date \_\_\_\_\_

REMARKS