



3. Original Description Vol. Page Where Recorded

4. Description of Corners: E-LD 1890 SET POST MKD.
 10" HEM. N. 31° E., 11 LKS.
 6" HEM. N. 61° W., 7 LKS.
 5" HEM. S. 87° E., 11 LKS. AND WITNESSES IN GOOD CONDITION
 12" SPRUCE, S. 22° W., 6 LKS.

5. Investigation Notes:

CORNER IS GONE. #995 WITH
 FOUND 10" HEMLOCK STUB N. 61° 30' E., 7 LKS. (ORIG.)
 VISIBLE MKS. S 11 BT ILLKS WITH
 FOUND ORIG 2 IN DEAD HEMLOCK STUB, N. 31° E.
 VISIBLE MKS. S 12 BT.
 FOUND 3 IN DEAD SPRUCE STUB, S. 22° W., 6 LKS. WITH A
 ROTTED FACE. DID NOT CHOP OPEN
 FIND THE ORIG S. E. BT STUMP IN ITS PROPER POSITION

7. Photo Identification
 Photo No. ETJ 6-209
 Ident. By: [Signature]
 8. Plane/Coordinate Position Data
 State Zone
 X
 Y
 Estab. By
 Field Book No.
 Where Filed
 9. Evaluation

CORNUA COLUET 108 011x9q

TILLAMOOK COUNTY REWITNESS

Leonard Whitmore is a Deputy County Surveyor accompanied to the witness
 identifiable positive monument found in connection with Field Book

12. Set By: [Signature] Title: [Signature]
 License Agency Date 12/77

13. Recorded By: [Signature] Volume:
 (Date) (City) (County)

14. Remarks:
 SET 1 1/2 IN. GALVANIZED PIPE AT CORNER POINT 2 FT ABOVE GROUND
 ON A 2.5% SOUTH SLOPE.
 NEW B.T.S.
 3 IN. HEM. N. 61° E., 16 LKS. MKD. X BT IN THE PRESENCE
 3 IN. HEM. N. 58° W., 4 LKS. MKD. X BT ED. GARY
 16 IN. HEM. S. 12° E., 149 LKS. MKD. TO CORNER S 13 BT BILL HEITSMAN
 4 IN. HEM. S. 87° W., 10 LKS. MKD. X BT WAYNE ABBEY

COMMENTS: