CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 12 and 13 (East side) T3N, R7W, W.M., Tillamook County, Oregon.

ORIGINAL

Stake (now missing), found 3"x3"x48" Fir post scribed \$18 R6W on E. \$12 T3N on NW and \$13 R7W on SW sides, from which a:

24" Hemlook bears N38°E 37 lks.; roots in place. (Marks reported destroyed by resurvey).

48" Fir bears \$680E 28 lks.; now 56" uproot. (Marks reported destroyed by resurvey).

destroyed by resurvey).

6" Hemlock bears \$46°W 35½ lks.; now 12" uproot, scribes T and BT remaining.

12" Hemlock bears N53°W 65 lks.; now 13" uproot, scribes BT remaining.

RESTORED

Set $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T3N R7W R6W S12 S13 S18 1953 RE2311," 33 inches in ground, with scribed post on N edge, in mound of stone, and from which a:

66" Fir stump bears N47°W 58.4 ft.; scribed T3N R7W, (previously scribed \$12 BT by unknown party).

60" Fir stump bears \$69°W 56.5 ft.; scribed T3N R7W RE2311, (previously scribed \$13 BT by unknown party).

67" Fir stump bears \$76°E 66.9 ft.; scribed T3N R6W, (previously scribed \$18 CC BT by unknown party). Destroyed scribes CC.

Oregon State Board of Forestry metal location poster on 66" Fir stump BT.

Set 4"x4"x72" white painted Cedar post 2 ft. East of pipe.

Dated May 31, 1955.

Restored by Richard Morris, Engineering Aide under my direction.

ERED PROFESS, ENGINEER 2311

OREGON

OUS W. AM

Present and witnessed by Lloyd Geraths
Forrest Logan
Robert Sturm

Booki