

CHAINS

REESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

Section corner common to Sections 19, 24, 25 and 30,
T3S, Rges. 9 and 10 W, W.M., Tillamook County, Oregon.

ORIGINAL

(No evidence of original corner found)

RESTORED 1887 (see county records)

(No evidence of restored corner found)

REESTABLISHED

Var. $21\frac{1}{2}^{\circ}E$

Set $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap
marked "OREGON STATE BOARD OF FORESTRY T3S, R10W
R9W, S24, S19, S25 S30 1957 RS 359," 32 inches in
ground; in mound of stone, and from which a:

12" Alder bears $N79^{\circ}E$ 91.7 ft.; scribed in bark
T3S R9W S19 BT.

21" Fir bears $N50\frac{1}{2}^{\circ}W$ 155.8 ft.; scribed T3S R10W
S24 BT.

22" Fir bears $S10\frac{1}{2}^{\circ}W$ 94.1 ft.; scribed T3S R10W
S25 BT RS 359.

20" Hemlock bears $S12^{\circ}E$ 110.8 ft.; scribed T3S
R9W S30 BT.

Set 4"x4"x60" white painted Cedar post 2' SE of pipe.

Oregon State Board of Forestry metal location poster on
21" Fir BT.

Also poster on 4"x4"x60" white painted Cedar post 28.8 ft.
N on S edge of road.

Dated February 21, 1957

Reestablished by *Richard Morris* under my direction.
Richard Morris, Transitman

REGISTERED
OREGON
LAND SURVEYOR

Arnold G. Gieson
NOV. 4, 1955
ARNOLD G. GIESON
359

Present and witnessed by Lloyd Geraths
Robert Sturm