CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

One Quarter corner common to Sections 33 and 34, T. 1N, R. 9W, W.M., Tillamook County, Oregon.

ORIGINAL

Post (now in place, badly rotted, scribes 1/4 s visible) from which a:

6" Alder bears S71°W 57 lks.; now 12" uproot, roothole in place, outline of rotted out face visible.

10" Alder bears N36°E 9 lks.; now 21", outline of rotted out face visible.

RESTORED

Var. 2120E

Set $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S33 S34 1957 RS401," 32 inches in ground, and from which a:

39" Fir bears S76°E 35.4 ft.; scribed 1/4 S34 BT RS401. 35" Fir bears S83°W 49.4 ft.; scribed 1/4 S33 BT.

Set original post on N edge of pipe.

Oregon State Board of Forestry metal location poster on 11"

Hemlock S47°E 6.1 ft. Set 3" x 4" x 60" white painted Cedar post 1.0' SE of pipe.

Dated October 25, 1957

Restored by

REGISTERED
OREGON
LAND SURVEYOR

Richard A. Morris 401

Present and witnessed by Robert Sturm
Harold Russell

Book I