CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 17, 18, 19 and 20, T. 2 S, R. 8 W, W.M., Tillamook County, Oregon

ORIGINAL

Basalt stone 16 x 12 x 10" (now missing, found l_{π}^{1} " x 48" capped iron pipe) from which a:

18" Hemlock bears N31W 21 lks.; now 24" rotted stub 3' high, no

10" Hemlock bears N57E 24 lks.; now 22" x 10' high stub, scribes S R8 visible.

10 Hemlock bears S39E 26 lks.; now 18" x 10' rotted stub, scribes R8 S20 visible (now 76 lks. distant).

16' Hemlock bears S12W 58 1ks.; now burnt and rotted shell 5' high, original axe work on edge of burnt out face, (now bears S25W).

RESTORED

Set above $1\frac{1}{4} \times 48^{\circ}$ iron pipe 38 inches in ground, in mound of stone, and from which a:

8" Noble fir bears S82W 7.3 ft.; scribed T2S R8W S19BT 42" Noble fir bears N88E 109.1 ft.; scribed T2S R8W S17 BT 6" Alder bears S44E 33.4 ft.; scribed T2S R8W S20 BT 14" Noble fir bears N61W 63.0 ft.; scribed T2S R8W S18 BT 6" Noble fir bears S2OW 14.5 ft., scribed RS359

Set 4 x 4 x 72" white painted cedar post 1' NW of pipe.

Oregon State Board of Forestry metal location poster on 8" N. Fir BT Also poster on east side 42" N. Fir BT.

Dated Jahuary 24, 1958

Restored by David Steenson, Engineering Aide

_under my direction.

REGISTERED OREGON LAND SURVEYOR

ARNOLD G. GIBSON

Present and witnessed by: Clarence Skog

Book I

330