ESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY

W One-sixteenth corner common to Sections 5 and 32, T. 3 & 4N, R. 9W, W.M., Clatsop & Tillamook counties, Oregon.

ESTABLISHED

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY W 1/16 S5 S32 1958 RE2311," 32 inches in ground, and from which a:

30 Hemlock bears N 29°E 50.1 ft.; scribed W 1/16 S32 BT. 26" Hemlock bears S 34° 30'W 27.0 ft.; scribed W 1/16 S5 BT, RE2311.

Oregon State Board of Forestry metal location poster on 21" Hemlock S39° E 9.1 ft. Also poster on 4 x 4 x 72" white painted Cedar post N89° 30°W 784.2 ft. on East edge of Hwy. #53.

REESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY

One-Quarter corner common to Sections 5 & 32, T. 3 & 4 N, R. 9W, W.M., Clatsop & Tillamook County, Oregon.

ORIGINAL

(No evidence of original corner found)

REESTABLISHED

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S5 S32 1958 RE2311," 33 inches in ground, and from which a:

48 Hemlock bears N55° 30'E 105.0 ft.; scribed 1/4 S32 BT. 20 Hemlock bears S87°W 26.3 ft.; scribed 1/4 S5 BT RE2311.

Oregon State Board of Forestry metal location poster on 28" Hemlock S32°W 29.0 ft.

Dated June 19, 1958

Reestablished by

Present and witnessed by

under my direction.

Engineering Aide II

J. F. Martin J. E. Wilson Rob't. Pryor

0. N. Olson

Book I