CHAINS

REESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY (See official plat)

One Quarter corner common to Sections 1 & 12, T. 3S, R. 7W, W.M., Tillamook County, Oregon.

ORIGINAL

(No evidence of original corner found)

REESTABLISHED

Var. 21是

Set 13" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S1 S12 1958 RS401", 12 inches in ground, in mound of stone 24" high, and from which a:

6" Fir bears S87W 6.87 ft.; scribed 1/4 S12 BT. 8" Fir bears N64E 16.76 ft.; scribed 1/4 S1 BT RS401.

Oregon State Board of Forestry metal location poster on 8^n Fir BT. Set 3^n x 4^n x 60^n white painted Cedar post 1.5' S.E. of pipe.

ESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY East one sixteenth corner common to Sections 12 and 13, T3S, R7W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21掘

Set 13" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY E 1/16 S12 S13 1958 RS401", 33 inches in ground, and from which a:

19" Fir bears N62W 12.66 ft.; scribed E 1/16 S12 BT RS 401. 18" Fir bears S32E 14.20 ft.; scribed E 1/16 S13 BT.

Oregon State Board of Forestry metal location poster on 18" Fir BT. Set 4" x 4" x 60" white painted Cedar post 1.5' N.E. of pipe.

Dated October 28, 1958

Established by

REGISTERED OREGON LAND SURVEYOR

Richard A. Morris

401

Present and witnessed by Robert Sturm
Ronald Schulson
Harold Russell

Book I

348

248