

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

One Quarter corner for Section 7 (West side) T1S,
R7W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Marked S.E. face of 24" x 24" x 30" boulder 1/4 X at corner point from
which a:

52" Fir bears S67 3/4 E 246.5 ft.; scribed 1/4 S7 BT RS401.

Oregon State Board of Forestry metal location poster on 52" Fir BT.
Set 4" x 4" x 54" white painted Cedar post 1.2' N.E. in mound of
stone.

Witness Corner for the Center West One Sixteenth
corner for Section 7, T1S, R7W, W.M., Tillamook
County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E


At a point S87°23'39"W 83.3' from the CW 1/16 corner point in the Wilson
River set a 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked
"OREGON STATE BOARD OF FORESTRY WC W 1/16 C---C 1958 RS401", 18 inches
in ground, in mound of stone 18" high, and from which a:

5" Alder bears S4 $\frac{1}{2}$ E 30.9 ft.; scribed in bark X BT.
12" Alder bears N20 $\frac{1}{2}$ W 47.4 ft.; scribed in bark X BT RS401.


Oregon State Board of Forestry metal location poster on 12" Alder BT.
Set 4" x 4" x 54" white painted Cedar post 1.0' N.W. of pipe.

Dated December 17, 1958

Established by



Richard A. Morris



Present and witnessed by R. Schulson
H. Russell
R. Cop