CHAINS

ESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY (See official plat)

Northwest One Sixteenth corner for Section 7, TIS, R7W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21部

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NW 1/16 S7 1958 RS401", 48 inches in ground, in N. track of old road, and from which a:

9" Alder bears $54\frac{1}{2}$ W 24.5 ft.; scribed in bark, NW 1/16 S 7 BT. RS401.65" Fir stump bears N33E 109.4 ft.; scribed NW 1/16 S7 BT.

Oregon State Board of Forestry metal location poster on 65" Fir stump BT. Also poster on 4" x 4" x 53" white painted Cedar post on N. edge of road N21E 6.9 Ft. from pipe.

Dated December 17, 1958

Established by

Present and witnessed by R. Schulson

R. Cop

H. Russell

REESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY (See official plat)

Section corner common to Sections 13 and 24 (East side), TlS, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

(No evidence of original corner found)

REESTABLISHED

Var. 21

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY TIS R8W R7W S13 S19 S24 1958 RS401", 33 inches in ground, in mound of stone, and from which a:

5" Fir bears N75 1/4 W 62.4 ft.; scribed X BT.

64" Fir stump bears S50 1/4 W 104.2 ft.; scribed TIS R8W S24 BT RS401.

Oregon State Board of Forestry metal location poster on 64" Fir stump BT. Set 4" x 4" x 50" white painted Cedar post 0.5' E. of pipe.

Dated December 17, 1958

Reestablished by

REGISTERED
OREGON
LAND SURVEYOR

Richard A. Morris

Present and witnessed by R. Schulson

H. Russell

R. Cop

Book I

360

360