

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)
East One Sixteenth corner common to Sections 22 & 27,
T2S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY E 1/16 S22 S27 1959 RS401", 33 inches in ground, and from which a:

6" Hemlock bears N51 1/2 W 21.5 ft.; scribed E 1/16 S22 BT RS401.
15" Hemlock bears S65 E 33.0 ft.; scribed E 1/16 S27 BT.

Oregon State Board of Forestry metal location poster on 6" Hemlock BT.
Set 4" x 4" x 56" white painted Cedar post 1.0' N.E. of pipe.

One Quarter corner for Section 26 (West side), T2S,
R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E


Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S26 1959 RS401", 34 inches in ground, and from which a:

15" Hemlock bears N52 1/2 E 18.1 ft.; scribed 1/4 S26 BT RS401


Oregon State Board of Forestry metal location poster on 8" Hemlock N78 E 14.8'
Set 4" x 4" x 56" white painted Cedar post 1.0' N.E. of pipe.

Dated April 14, 1959 *RM*

Established by



Richard A. Morris



Present and witnessed by H. Russell
R. Cop