CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON—DEPARTMENT OF FORESTRY (See official plat)

Center West Southwest One Sixty-fourth corner for Section 13, TlN, RlOW, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 x 36 galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY CW-SW 1/64 S13 1962 RS401", 18 inches in ground, in mound of rock, and from which a:

38" Alder bears N29°W 58.0 ft.; scribed CWSW 1/64 S13 BT.
18" Alder bears N44°E 56.5 ft.; scribed CWSW 1/64 S13 BT RS401.

This corner lies 3' from waters edge on west bank of Moss Creek.

Set 4" x 4" x 60" white painted Cedar post 2 ft. NW of corner pipe.

Oregon State Forestry Department metal location poster on 38" BT.

Also poster on white site post, N19°W 69.2, on west end of Moss Ck. bridge.

* * * * * * * * *

West West One Sixty-fourth corner common to Sections 13 and 24, TlN, RlOW, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY W-W 1/64 S13 S24 1962 RS401", 30 inches in ground, and from which a:

12" Hemlock bears N38°W 7.9 ft.; scribed W W 1/64 S13 BT.
32" Hemlock bears S41°E 36.2 ft.; scribed W W 1/64 S24 BT RS401.

Set 4" x 4" x 60" white painted Cedar post 1 ft. SW of corner pipe. Oregon State Forestry Department metal location poster on 12" BT.

Dated June 19, 1962

Established by_

Billy W. Davis

_under my direction.

O R E G O N LAND SURVEYOR

Richard A. Morris

401

Present and witnessed by D. Fletcher and C. Curl

64. 2.

429

Book I