CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON-DEPARTMENT OF FORESTRY (See official plat)

Center North One-sixteenth corner for Section 24, TlN, RlOW, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 C--- C S24 1962 RS401", 32 inches in ground, in mound of rock, and from which a:

20" Hemlock bears N652E 9.9 ft.; scribed CN 1/16 S24 BT. 7" Hemlock bears N80W 12.3 ft.; scribed CN 1/16 S24 BT RS401.

Set $4^n \times 4^n \times 56^n$ white painted Cedar post 2.0 ft. SW of corner pipe. Oregon State Forestry Department metal location poster on 14" Hemlock N89E 5.7 ft.

Present and witnessed by D. Fletcher, C. Curl

North One-sixteenth corner common to Sections 23 and 24, TIN, RIOW, W.M., Tillamook County, Oregon.

_* * * * * * * *

ESTABLISHED

4.1/6

Var. 212E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 S23 S24 1962 RS401", 33 inches in ground, and from which a:

16" Hemlock bears S41E 2.2 ft.; scribed N 1/16 S24 BT. 13" Hemlock bears S152W 18.2 ft.; scribed N 1/16 S23 BT RS401.

Set 4" x 4" x 56" white painted Cedar post 2.0 ft. SW of corner pipe. Oregon State Forestry Department metal location poster on 15" Hemlock N74W 2.8 ft.

Dated December 21, 1962

Allan E. Duncan, Forestry Aide under my direction. Established by __

Present and witnessed by D. Fletcher

REGISTERED OREGON LAND SURVEYOR

Richard A. Morris