

CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON-DEPARTMENT OF FORESTRY
 (See official plat)
 Center South One Sixteenth corner for Section 17, T3S, R8W,
 W.M., Tillamook County, Oregon.

CS 1/16
 17-3-S-8

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S 1/16 C---C S17 1961 RS401", 32 inches in ground, and from which a:

11" Fir bears N34W 19.5 ft.; scribed CS 1/16 S17 BT RS401.
 30" Fir bears S35 1/2 E 6.6 ft.; scribed CS 1/16 S17 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.E. of corner pipe. Oregon State Forestry Department metal location poster on 30" Fir BT.

* * * * *

Southeast One Sixteenth corner for Section 17, T 3S, R8W,
 W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

SE 1/16
 17-3-S-8


Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SE 1/16 S17 1961 RS401", 30 inches in ground, on E bank of logging road, and from which a:

22" Fir bears S15 1/2 E 161.9 ft.; scribed SE 1/16 S17 BT RS401.
 20" Fir bears N24W 266.0 ft.; scribed SE 1/16 S17 BT.


Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.W. of corner pipe. Oregon State Forestry Department metal location poster on 20" Fir BT.

Dated January 22, 1962

Established by



Richard A. Morris



Present and witnessed by A. Duncan
 E. Danielson

462