CHAINS

ESTABLISHED CORNERS FOR STATE OF CREGON-DEPARTMENT OF FORESTRY (See official plat)

Center South One-sixteenth corner for Section 8, TLS, RSW, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 212E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY CS 1/16 C-C SS 1962 RS401", 32 inches in ground, in mound of rock, and from which a:

5" Spruce bears S31½E 20.9 ft.; scribed CS 1/16 S8 BT. 17" Alder bears S34½W 11.5 ft.; scribed CS 1/16 BT RS401 S8. Wigger Jack Creek bears West 40.5 ft.; course South.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. NW of corner pipe.

Oregon State Forestry Department metal location poster on 5" Spruce BT.

* * * * * * * * *

West One-sixteenth corner common to Sections 8 and 17, TIS, RSW, W.M., Tillamook County, Oregon.

ESTABLISHED

4,46

Var. 211E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY W 1/16 S8 S17 1962 RS401", 32 inches in ground, in mound of rock, and from which a:

21" Spruce bears S25W 163.1 ft.; scribed W 1/16 S17 BT RS401. 48" Hemlock bears N142W 181.1 ft.; scribed W 1/16 S8 BT.

Corner is approx. 60' South of power line on edge of pasture land.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. NW of corner pipe. Oregon State Forestry Department metal location poster on 21" Spruce BT.

Dated June 27, 1962

Established by _____

13 Vavis

_ under my direction.

B. Davis, Transitman

Present and witnessed by D. Fletcher

O R E G O N LAND SURVEYOR

Richard A. Morris

401

482

Book I