

CHAINS

RESTORED CORNER FOR STATE OF OREGON-DEPARTMENT OF FORESTRY

Section corner common to Sections 20, 21, 28 and 29,
T3S, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

Basalt stone 18" x 14" x 7" (missing) from which a:

- 36" Fir bears N74W 101 lks.; now 51" stub 20' high, scribes T3S R8 S20 BT visible.
- 34" Fir bears N57E 68 lks.; missing.
- 28" Fir bears S58E 43 lks.; now 35" stub 15' high, face and scribes rotted away.
- 40" Fir bears S14W 25 lks.; now 48" stub 20' high, scribes T3S R8W S29 B remaining.

RESTORED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T3S R8W S20 S21 S29 S28 1961 RS401", 30 inches in ground, in small mound of stone, and from which a:

- 11" Fir bears S9 1/2 E 14.8 ft.; scribed T3S R8W S28 BT RS401.
- 11" Fir bears S64W 31.4 ft.; scribed T3S R8W S29 BT.
- 12" Fir bears N65 1/2 W 19.9 ft.; scribed T3S R8W S20 BT.
- 14" Fir bears N31E 24.9 ft.; scribed T3S R8W S21 BT.

Oregon State Forestry Department metal location poster on 28" Fir N65E 5.9 ft.

Set 4" x 4" x 54" white painted Cedar post 1.6' N.W. of pipe.

Dated November 10, 1961

Restored by Harold J. Russell under my direction.
Harold Russell, Engineering Tech.



Richard A. Morris
MAY 10, 1957
Richard A. Morris
401

Present and witnessed by A. Duncan