XHAINSX

Sec cor 18 17 T6SR9W WM From remaining B.T. all windthrown or logged-out stumps I set a new cor. tree A Hemlock 10" dia

mkd. T6SS7 on NW

S8 on NE

R9WS17 on SE

S18 on SW

This cor tree is visible from Ray & Adams road about 1-2 miles up road from juncture with Murphy's Road - cor tree is spike topped and broken. Only green tree in vicinity. In the presence of John S. Forrest and James G. Reid.

1/4 cor 14 TLSRLOW WM

From remaining B.T. Stump in badly decayed condition called 50" fir S650E 252 lks, I set  $1-\frac{1}{2}$ " iron pipe 5' long 2' in ground for  $\frac{1}{4}$  sec cor from which:

A spruce 40" dia bears S65°E 158.71 distant

mkd. 4 SBT

A spruce 41" dia. bears S4°E 102.1' distant

mkd.  $\frac{1}{4}$  SBT. This cor is a fence cor bearing Sl4°E from the Krietz farm house on U.S. 101 hiway between Hebo & Cloverdale. No substantial trees were available for proper designation of this cor so placed two sound trees in Sec 23 B.T. for Sec 14 is:
An alder 8" dia N47°E 52.18' distant

mkd.  $\frac{1}{4}$  SBT.

(This tree in swamp-clump of alder behind Krietz house.)

Twp. cor TISR8W WM T2SR8W WM I set an irom pipe 5' long, 2' in ground for cor from which:
A spruce 3" dia bears N79°E 35' distant mkd. TlSS31

No other trees to be had for witnessing. The two G.L.O. witnesses remain but in an advanced state of deterioration. Several alders were pruned up about 29' hi to the N & E of the cor. ( In the presence of John S. Forrest and James G. Reid.)

20 | 21 29 | 28 T2SR8W WM

From remaining B.T's a dead cedar NE

a live cedar NW

a live alder SW

I set an iron pipe  $1-\frac{1}{2}$ " dia 5' long 2' in ground for the corner from which

A cedar 8" dia bears N72°E 8' distant

mkd. T2SR8W S 21 BT. A red fir 20" dia bears S36°E 39' distant

mkd. T2SR8W S 28 BT. This corner is found to be some 1350' S & 600' odd feet E of the assumed position of 80 ch. south of the cor to the N. The cor lies 1.5 ch up on the south bank of a small creek running S 30° E.

In the presence of John S. Forrest, James G. Reid and Garth Cross.

Sec cor 10 | 11 15 | 14 T5SR1QW WM

This corner was completely logged over & all original witness trees together with corner post. were obliterated. I reset this corner in place as witnessed by U.S.F.S. Location poster placed prior to logging & upon the statements of Mervin Whitmore, U.S.F.S., who found & posted the original corner & Mabry Ogle who owns the land and was present at the corner prior to the logging.

I set  $1-\frac{1}{2}$ " iron pipe 5' long,  $2-\frac{1}{2}$ ' in ground for sec cor from which: A hemlock 23" dia bears S8°W 18.5' distant

mkd. T5SR10W S 15 BT

A hemlock stump 25" dia bears S60°E 35.8' distant mkd. T5SR1OW S 14 BT

BOOK 2 '

32