

Court Surveyor's Record, Tillamook County, Oregon

(51)

CHAINS FEET	
	SURVEY FOR THE OREGON STATE BOARD OF FORESTRY OF TOWNSHIP LINE BETWEEN SECTIONS 13 & 24 OF T1N R6W AND SECTIONS 18 & 19 OF T1N R5W.
	RETRACEMENT:
	Beginning at the section corner to Sections 24, 25, 19 & 30, T1N, R 5 & 6 W WM., determined by a fir snag 38 inches in diameter, marked R6W T1N S26 (the scribe S26 is erroneous and should have been S25) from which was found: A larch 18" in diam. bearing S 39° E a distance 8.6 ft. with face burnt but scribe R S3 visible.
	Part of a burnt hemlock brs. S 52° W a distance of 15.2 ft.
	A hemlock stump 14 inches in diam. brs. N 65° E a distance of 13.5 ft.
	A hemlock stump 18 inches in diam. brs. N 24° W a distance of 31.3 ft.
	Starting with a compass bearing, variation 22° E using a K & E Light Mtn Transit North on a random line between sections 19 & 24 T1N R 5 & 6 W.
Random line Dist., feet	
1320	Set temp. stake.
2640	The 1/4 corner between Secs. 19 & 24 bears S 72° 58' E a distance of 12.7 ft. The corner determined by a stone 18" x 8" x 5" marked 1/4 on under side.
2820	Top of ridge bears E & W.
3952	Stream, 3 ft. wide, course N 40° E.
3960	Temp. stake.
3986	Stream, 2 ft. wide, course S 50° E.
5280	Set temp. stake, find no evidence of corner to secs. 13, 18, 24, 19.
	Continue North between secs. 13 & 18. Beginning new measurement.
935.4	Temp. stake on N. edge of road run NE & SW.
1320	Set temp. stake.
2091.2	N 01° E a distance of 450.0 ft.
	(Continued on page _____)
BOOK 2	
51	
	51