Count Turveyor's Record, Tillamook Count Dregon

Page (126)

CHAINS	
2622.6	Intersect the true line S 89 $^{\circ}$ 52' W through the center of sec. 13 at a point 2656.0 feet S 89 $^{\circ}$ 52' W of the $\frac{1}{4}$ cor. to secs. 13 & 18.
	At the center of sec. 13 the point of intersection of true lines.
	Set an iron pipe $1\frac{1}{2}$ inches in diameter, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped $0\frac{1}{4}$ S13, 1949, 199
	from which:
	A cedar snag, 16 inches in diameter, bears S 24° W, a distance of 19.0 feet. Scribed: C ₄ S13, 199.
	A location poster on a cedar snag, 13 inches in diameter, bears S 58° E, a distant of 24.6 feet and marked: Sec. 13 TlN R6W C4 Cor. 24.6 feet N 58° W.
3959.9	Point for center south 1/16 corner. Adjustment from temporary stake (3960.0) - North 0.5 feet, East 59.9 feet.
and the second s	At the point for CS 1/16 cor.
	Set an iron pipe, la inches in diameter, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: S C-C 1/16 S13, 1949, 199.
	from which:
	A fir snag, 50 inches in diamter, bears S 68° E, a distance of 54.0 feet, scribed: S 1/16 S 13 BT 199.
	Placed a mound of stone around monument.
er Arten de la constante de la	Establishment of CE 1/16 cor. sec. 13, TlN, R6W.
	Relative to the compass bearing of the random line, the true line from the $\frac{1}{4}$ cor. between secs. 13 & 18, TlN, R5 & 6W to the center of sec. 13, bears S 89052° W, a distance of 2656.0 feet. Mid-point 1328.0 feet.
1328.0	Point for center east 1/16 cor. sec. 13. Adjustment from temporary stake set at 1320.0 on random line - South 37.6 feet West 8.4 feet.
	At the point for CE 1/16 cor.
	Set an iron pipe, $1\frac{1}{2}$ inches in diameter, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: E 1/16 C-C S13 1949 199.
	from which:
	A fir snag, 45 inches in diameter, bears S 23° W, a distance of 38.0 feet, scribed: E 1/16 199 BT. Placed a metal location poster on a fie snag, 18 inches in diameter,
:	and marked it: Sec 13 TlN R6W CE 1/16 8.3 ft N 68° E.
	Subdivision of SE of Sec. 13.
	Beginning at the S 1/16 cor between secs. 13 & 18 TlN R5 & 6W, W.M. established by survey of the sec. line between secs. 13 & 18 TlN R5 & 6W.
A 4	

BOOK 2