Cour Surveyor's Record, Tillamook Cour Oregon

Page (127)

CHAINS	
and the state of t	Starting with a compass bearing, variation 22° E.
	West on a random line through the center of the SE4 of Sec. 13.
1320.0	Set temporary stake.
2640.0	CS 1/16 cor. of sec. 13 bears N 9008 E, a distance of 44.8 feet.
	Relative to the compass bearing of the random line, the true line bears N 89002 W, a distance of 2633.3 feet.
1316.6	Mid point of true line, set temporary stake. Adjustment from temporary stake (1320) - North 22.1 feet East 3.5 feet.
	Established direction of true line.
And all all and a company of the com	Beginning at the E 1/16 cor. between secs. 13 & 24, TlN, R6W, W.M. determined on adjustment of the section line between secs. 13 & 24, TlN, R6W.
v dilludit Zivadilaravasa	Starting with a compass bearing, variation 22° E.
meren da maria de la composição de la co	North on a random line through the center of the east half of sec. 13.
1320.0	Set temporary stake.
2640.0	CE 1/16 cor. bears S 82011' E a distance of 62.5 feet.
5280.0	E 1/16 cor. between secs. 12 & 13 bears S 80 59° E a distance of 124.3 feet.
	Relative to the compass bearing of the random line, the true line, from the E 1/16 cor. between secs. 13 & 24 to the CE 1/16 of sec. 13, bears N Ol ^O 21' E, a distance of 2632.2 feet.
1316.1	Mid point of true line, set temporary stake. Adjustment from temporary stake on north random 1320.0 South 4.2 feet, East 31.0 feet, Established direction of true line.
and populations and the second	S 01°21' W. a distance of 8.4 feet.
1307.7	Intersect the true line N 89°02° W through the center of the SE2 of Sec. 13 at a point 1316.6 feet N 89°02° W. of the S 1/16 2005 - 13 between secs. 13 & 18, TlN, R5 & 6W.
**************************************	At the SE 1/16 cor point the intersection of true lines through the center of SE sec. 1.3
	Set a la inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: SE 1/16 S13 1949 199.
· ·	from which:
and the state of t	A fir snag, 49 inches in diameter, bears S 60° E, a distance of 70.8 feet, scribed: SE 1/16 S 13 1949 199.
The second particular and the second particu	Placed a metal location poster on a fir stump, 34 inches in diam., & marked it: Sec 13 TlN R6W SE 1/16 cor 18.6 ft N 430 W.
- C	
APPROPRIES AND THE PROPERTY FOR THE PROP	
1	