CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to sections 14, 15, 22, and 23, Township 2 North, Range 9 West, W.M., Tillamook County, Oregon.

ORIGINAL

Post, now missing, from which a:

9" Hemlock bears N43W 54 lks; now 9" root stub.

40" Hemlock bears N36E 11 lks; now 55" stub 20" high. 14" Hemlock bears S18E 17 lks; now 16" stub 2.5" high.

24" Hemlock bears S69W 98 lks; now 52" stub 14" high S75W, exposed scribe marks TZN R9W S22 BT.

RESTORED CORNER AND BEARING TREES

Set 1^{1}_{S} x 36° galvanized iron pipe with 3° bronze cap marked "OREGON STATE BOARD OF FORESTRY T2N R9W S15 S14 S22 S23 1952 2311," $2\frac{1}{2}$ ' in ground, from which a:

10" Hemlock bears S71W 34.4"; scribed T2N R9W S22 BT RE 2311.

43° Fir snag bears S43E 7.6'; scribed T2N R9W S23 BT. 14° Fir stub 5' high bears N22°30'W 52.8'; scribed S15 BT. (No other BT's available.)

Placed an Oregon State Board of Forestry metal location poster on original BT now, 52" Hemlock stub and marked it: Sec 22 Tan Rew Sec Cor 64 Ft. N75E.

Dated June 12, 1952.

This corner was restored by under my direction.

Don D. Davis Assistant Forest Engineer



Present and witnessed by

Richard A. Morris Compassman

Present and witnessed by