

Cour Surveyor's Record, Tillamook Cou Oregon

257

T 3 S. R 9 W

Rewitnessed Corners

Mervin Whitmore, U.S. Forest Serv.

CHAINS/		
Sec. Cor.		Set iron pipe, from which
22   23		A 50" dead fir bears N 25° E, 140 lks. With old scribe marks. A 48" dead fir bears S 65° E, 130 lks. With old scribe marks. The bearing and distance to this tree is not mentioned in the original notes.
27   26		A 16" fir bears N 25° E, 50 lks. Marked T3S R9W S23 BT (New BT) This tree is in line with the original 50" dead fir above. A 16" fir bears S 12° W, 6 lks. Marked T3S R9W S27 BT (New BT) A 14" alder bears N 52° W, 41 lks. Scribed in bark T3S R9W S22 BT (New BT) A 20" alder bears S 47° E, 13 lks. Scribed in bark T3S R9W S26 BT (New BT). This corner sets 16 lks. <sup>south</sup> <del>west</del> of the bottom of a deep ravine These course is N 60° W.
		In the presence of Bill Heady. March 4, 1952.
Sec. Cor.		Set iron pipe, from which
36   31	Rgs. 8&9W	A 36" dead fir bears East, 19 lks. Marked $\frac{1}{2}$ S. Other marks rotted off (Old BT) <del>22 lks.</del> A 48" dead fir bears S 20° W. <sup>A</sup> With old ax blaze, scribing burned off (Old BT). A 10" fir bears S 75° W, 7 feet. Marked $\frac{1}{2}$ S 36 BT (New BT) A 12" fir bears S 80° E, 11.3 feet. Marked $\frac{1}{2}$ S 31 BT (New Bt)
		In the presence of Martin Chaffee. Sept. 10, 1952.
$\frac{1}{4}$ Sec. Cor.		Set iron pipe, from which
7.5. 2 3/8 S		Remains of 14" fir stump S 42° E, 13 lks. Marked BT (Old BT) Remains of 10" fir stump N 79° W, 6 lks. Marked rotted off (Old BT) A 20" fir S 31° E, 25 feet. Marked $\frac{1}{2}$ S 4 BT (New BT) <i>This is the <math>\frac{1}{4}</math> sec. cor. to sec. 4.</i>
33		In the presence of Marvin Thomason. April 2, 1953
4		<i>The <math>\frac{1}{4}</math> sec. cor. for sec. 33 bears N. 89° 47' W. 3.20 chains. (Found)</i>
Sec. Cor.		Set iron pipe, from which
23   24		A 48" dead fir and fallen, S 63° E with scribe mark "B". Other marks rotted off (old BT). A 7" fir, N 51° E, 14 $\frac{1}{2}$ feet. Marked $\frac{1}{2}$ S 24 BT (New BT) A 26" fir, S 81° W, 48 feet. Marked $\frac{1}{2}$ S 23 BT (New BT)
		In the presence of Howard E. Taylor. Sept. 24, 1952.
Sec. Cor.		Set iron pipe, from which
13		A 15" alder, N 70° E, 63 lks. Scribe marks in bark (Old BT) A 16" alder, S 25° E, 93 lks. Fallen. Marked BT (Old BT) A 22" fir, S 76° E, 26 feet slope distance. Marked $\frac{1}{2}$ S 24 BT (New BT) A 36" fir, N 26° W, 40 feet slope distance. Marked $\frac{1}{2}$ S 13 Bt (New BT).
24		In the presence of John Borba.. April 13, 1953.
Sec. Cor.		Set iron pipe, from which
Rgs. 8&9W		A 40" dead fir, N 35° W (not 55° W as per notes), 33 lks. Marked R9W other marks rotted off. (Old BT) A 24" dead fir, S 60° W, 23 lks. Old ax blaze, scribe marks burned off. (Old BT) A 32" fir, N 30° W, 18 feet. Marked T3S R9W S24 BT (New BT) A 23" fir, S 71° E, 7.8 feet. Marked T3S R8W S30 BT (New BT)
24   19		In the presence of John Borba. April 23, 1953.
25   30		