Surveyor's Record, Tillamook Couv Cour Oregon

	T 3 S. R 10 W
	Rewitnessed Corners
######/ Sec. Cor. 22 23 27 26	Mervin Whitmore, U.S. Forest Serv. Set a fir limb post, from which A 56" dead fir, S 20° W, 34 lks dist. Marked BT, other mks gone A 22" fir, S 30° W, 26½ lks. Marked T3S R16W S27 BT (New BT) A 22" fir, S 63½°E, 23 lks. Marked T3S R16W S26 BT (New BT) A 12" fir, N 44° E, 25 lks. Marked T3S R10W S23 BT (New BT) A 12" fir, N 28° W, 15½ lks. Marked T3S R10W S22 BT (New BT) In the presence of Elmer Kimber and Kenneth Ray. March 20, 1952.
22 27	Set iron pipe, from which A 32" dead fir, S 72° W, 10 lks. Marked \(\frac{1}{4}\)S BT (Old BT) A 30" fir, N 7° W, 28 lks. Marked \(\frac{1}{4}\)S BT (New BT) A 24" fir, S 7° E, 18 lks. Marked \(\frac{1}{4}\)S BT (New BT) In the presence of Elmer Kimber and Kenneth Ray. March 19, 1952.
½ Sec.Cor	Set a fir limb post on west side of old rotten hemlock stump, which shows an ax blaze with scribe marks visible, but not legible. (Old tree marked for the \$\frac{1}{4}\$ Section Corner), from which A 30" fir, N 50 W, 26 lks. Marked \$\frac{1}{4}\$S 22 BT (New BT) A 20" fir, S 100 E, 60 lks. Marked \$\frac{1}{4}\$ S23 BT (New BT)
	In the presence of Elmer Kimber and Kenneth Ray. March 21, 1952.

BOOK 2

258