## Cour Surveyor's Record, Tillamook Cour Oregon

## CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

C-N-N-NE 1/256 corner for Section 14 (S.W. corner of the NW-NW-NE-NE-) TIN, RIOW, W.M., Tillamook County, Oregon.

## ESTABLISHED

Var. 21 E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY C-N-N-NE 1/256 S14 1959 RS401", 33 inches in ground, in mound of stone, and from which a:

5" Alder bears NISE 13.8 ft.; scribed in bark, 1/256 SL4 BT. 6" Alder bears S66E 28.4 ft.; scribed in bark, 1/256 SL4 BT RS401.

Oregon State Board of Forestry metal location poster on 5" Alder BT. Set 4" x 4" x 60" white painted Cedar post 1.0' S.E. of pipe. Corner lies on E. edge of bottom land and 11.0' E. of Road.

South One Sixteenth corner common to Sections 11 and 12, TlN, RlOW, W.M., Tillamook County, Oregon.

## ESTABLISHED

Var. 21班

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY S 1/16 S11 S12 1959 RS401", 33 inches in ground, and from which a:

24" Hemlock bears NIW 10.5 ft.; scribed S 1/16 S11 BT RS401.

28" Hemlock bears S39E 20.1 ft.; scribed by Longview Fibre Co. and partially grown over (1/16 S12 BT)

28" Hemlock stump bears N54W 33.7 ft.; scribed by Longivew Fibre Co. 1/16 Sll BT.

3/4" x 24" Stainless steel pipe bears S7 W 8.0 ft.; previously set by Longview Fibre Co.

Oregon State Board of Forestry metal location poster on 24" Hemlock BT. Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of 12" corner pipe.

Dated December 30, 1959

Established by

REGISTERED OREGON LAND SURVEYOR

MAY 16. 1957 Richard A. Morris

Present and witnessed by R. Cop

E. Nylund

BOOK 2