**CHAINS** 

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY (See official plat)

Center North One-sixteenth corner for Section 1, TlN, RlOW, W.M., Tillamook County, Oregon.

## **ESTABLISHED**

Var. 212E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 C—C Sl 1961 RS401", 33 inches in ground, and from which a:

10" Hemlock bears S892E 41.2 ft.; scribed CN 1/16 S1 BT.
11" Hemlock bears N36W 18.8 ft.; scribed CN 1/16 S1 BT RS401.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.E. of corner pipe. Oregon State Board of Forestry metal location poster on 9" Spruce S45W 2.1"

\* \* \* \* \* \* \* \* \* \*

North One-sixteenth corner common to Sections 1 and 6, TlN, R9 & 10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 EE

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY N 1/16 S1 S6 1961 RS401", 12 inches in ground, in mound of rock 2' high, and from which a:

52" Hemlock bears S51W 53.5 ft.; scribed N 1/16 S1 BT RS401.
6" Fir bears S66E 87.7 ft.; scribed N 1/16 S6 BT.

Set 4" x 4" x 52" white painted Cedar post 1.5 ft. S.E. of corner pipe. Oregon State Board of Forestry metal location poster on 10" Alder S9W 7.8 ft.

Dated February 27, 1960

Established by

REGISTERED
OREGON
LAND SURVEYOR

Richard A. Morris

Present and witnessed by R. Cop

G. Nylund

R. Schildknecht

100

BOOK 2