

3
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

	CHAINS	Retracement, Range Line, T. 5 S., bet. Rs. 10 and 11 W.							
	40.06	<p>Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.</p>							
	1.04	N. 0° 42' W., bet. secs. 1 and 6.							
	11.50	Descend 60 ft. over gradual N. slope, through open pasture land.							
	16.20	Wire fence, bears E. and W.							
	16.825	Top of bank and leave open pasture land, edge bears NE. and SW.; descend 105 ft. over steep NW. slope, through heavy timber and dense undergrowth.							
	80.12	High water line on SE. shore of Nestucca Bay, bears NE. and SW.; thence by triangulation across bay.							
<hr/>									
	1.50	<p>Point for the meander cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.</p>							
	2.50	The true point for the cor. of Tps. 4 and 5 S., Rs. 10 and 11 W., at proportionate distance in latitude and record distance in departure based on Wilkes' 1924 record; there is no remaining evidence of the original corner. The corner falls below the high water line of Nestucca Bay where it is impracticable to establish a permanent monument.							
<hr/>									
	3	<p>Retracement of a Portion of the Range Line, T. 4 S., bet. Rs. 10 and 11 W., Willamette Meridian, Oregon (Retracing the 1872 survey by John W. Meldrum, the 1879 survey by Henry Meldrum, the 1922 retracement by Lincoln E. Wilkes, and the 1924 dependent resurvey by Lincoln E. Wilkes)</p>							
	1.50	From the true point for the cor. of Tps. 4 and 5 S., Rs. 10 and 11 W.							
	2.50	N. 0° 31' E., bet. secs. 31 and 36.							
	3	Across tide flat.							
	1.50	High water line on NW. shore of Nestucca Bay, bears E. 40° E. and S. 30° W.; ascend slightly over sandy bank.							
	2.50	Point selected for the witness cor. to the cor. of Tps. 4 and 5 S., Rs. 10 and 11 W.							
	3	Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the sand, firmly set in a mixture of concrete and rocks, 2½ ft. diam. at the surface, 2 ft. deep, with brass cap md.							
<hr/>									
	3	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>W C</td> </tr> <tr> <td>T 4 S</td> </tr> <tr> <td>R 11 W R 10 W</td> </tr> <tr> <td>S 36 S 31</td> </tr> <tr> <td>S 1 S 6</td> </tr> <tr> <td>T 5 S</td> </tr> <tr> <td>1962</td> </tr> </table>	W C	T 4 S	R 11 W R 10 W	S 36 S 31	S 1 S 6	T 5 S	1962
W C									
T 4 S									
R 11 W R 10 W									
S 36 S 31									
S 1 S 6									
T 5 S									
1962									
	3	See Map F-40-205							

500M - 3 11