

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

	CHAINS	Retracement, Range Line, T. 4 S., bet. R. 10 and 11 W.
		from which
		A spruce, 24 ins. diam., bears N. $53\frac{1}{2}$ ° E., 9.52 lbs. dist., mkd. X BT.
		The top of Haystack Rock, bears N. $20^{\circ} 40'$ W.
40.06		The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with an iron post set by Wilkes in 1924, 1 in. diam., the top 12 ins. below the surface of the sand, firmly set, with brass cap mkd.
		S 36 S 31 1924
		Rehabilitate this cor. by pouring a mixture of concrete and rocks, 2 ft. diam., 15 ins. deep, around the iron post, with brass cap protruding 1 in. above the surface.
		Retracement of a Portion of the Township Line, bet. Tps. 4 and 5 S., R. 10 W., Willamette Meridian, Oregon (Retracing the 1872 survey by John W. Meldrum, and the 1922-1924 retracement by Lincoln E. Wilkes)
		From the E-E 1/64 sec. cor. of secs. 6 and 31, perpetuated with an iron wagon tongue, protruding 3 ft. above the ground, firmly set, at record bearing and distance from the original 1872 bearing tree:
		An uprooted spruce, 49 ins. diam., bears N. 10° E., 104 lbs. dist., with axe marks visible on partially opened blaze.
		and a bearing tree mkd. by Wilkes in 1922
		A spruce, 52 ins. diam., bears S. 89° W., 90 lbs. dist., with scribe mark S visible on partially opened blaze.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		S 31 E-E 1/64 S 6 1922
		from which
		A spruce, 7 ins. diam., bears N. 16° E., 112 lbs. dist., mkd. E-E 1/64 S31 BT.
		N. $89^{\circ} 26'$ W., bet. secs. 6 and 31.
See Map F-40-205		
37		

See pages 1-6 of Book 3 Pg 35 for add'l info.