

Dependent Resurvey, Portion of W. Bdy., T. 4 S., R. 7 W.

CHAINS	
12.30	Creek, 2 lks. wide, course N. 75° E.; asc. 20 ft. over SE. slope.
14.00	Spur, slopes NE.; desc. 240 ft. over steep rocky NE. slope.
19.34	Point for the S 1/16 sec. cor. of secs. 7 and 12. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 12 S 7 1965
	from which
	A fir, 14 ins. diam., bears S. 49° E., 94 lks. dist., mkd. S1/16 S7 BT.
	An alder, 20 ins. diam., bears N. 54° W., 71 lks. dist., bark scribed S1/16 S12 BT.
	Descend 260 ft. over steep NE. slope, changing to gradual N. slope.
31.20	Creek, 1 lk. wide, course N. 65° E.; desc. 35 ft. over NE. slope.
34.60	Creek, 1 lk. wide, course N. 35° E.; desc. 25 ft. over NE. slope.
36.95	Creek, 2 $\frac{1}{2}$ lks. wide, course N. 30° E.; desc. 5 ft. along E. slope.
38.47	Small ravine, drains N. 75° E.; asc. 5 ft. over SE. slope.
38.68	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, protruding 8 ins. above the ground, with brass cap mkd. and witnessed as described in the official record of the 1933 resurvey.
	N. $0^{\circ} 28'$ W., beginning new measurement.
	Ascend 10 ft. over gradual SE. slope.
0.70	Top of ascent, slopes E.; desc. 100 ft. over NE. slope.
6.50	Left bank of Nestucca River, bears NW., curving to N., and S. 80° E., course N.; continue along left bank over rocky river bottom.
10.60	Same left bank, bears N. 15° E. and S. 15° W., curving to S.; asc. 35 ft. over SE. slope.
14.40	Top of ascent, slopes E.; desc. 20 ft. over NE. slope changing to gentle N. slope.
19.60	Point for the N 1/16 sec. cor. of secs. 7 and 12. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 12 S 7 1965