

Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS

T 4 S R 7 W
 S 17 | S 16
 S 20 | S 21
 1965

from which

A fir, 26 ins. diam., bears N. 74° E., 119 lks.
 dist., mkd. T4S R7W S16 BT.

A fir, 29 ins. diam., bears S. 52° E., 80½ lks.
 dist., mkd. T4S R7W S21 BT.

A fir, 37 ins. diam., bears S. 37° W., 59 lks.
 dist., mkd. T4S R7W S20 BT.

An alder, 14 ins. diam., bears N. 38° W., 28 lks.
 dist., bark scribed T4S R7W S17 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, alder, cascara, wild cherry and maple;
 undergrowth, vine maple, salal, fern, nettle, Oregon
 grape, salmonberry, devil's club, hazel and blackberry.

From the cor. of secs. 15, 16, 21, and 22, perpetuated
 and recorded by Leo J. Martin, Registered Land Surveyor
 No. 363, in 1965, with a galvanized iron pipe, ¾ in.
 diam., protruding 12 ins. above ground, firmly set
 alongside the original basalt stone, 14 x 9 x 7 ins.,
 firmly set 8 ins. in the ground, mkd. with 3 notches on
 E. and 3 notches on S. edge, from which bearing trees
 mkd. by Martin:

A fir, 12 ins. diam., bears N. 82° E., 9½ lks.
 dist., mkd. 363 T4S R7W S15 BT on open blaze.

A fir, 17 ins. diam., bears S. 30½° E., 82 lks.
 dist., mkd. 363 T4S R7W S22 BT on open blaze.

A fir, 24 ins. diam., bears S. 44½° W., 23 lks.
 dist., mkd. 363 T4S R7W S21 BT on open blaze.

A fir, 10 ins. diam., bears N. 46½° W., 14½ lks.
 dist., mkd. 363 T4S R7W S16 BT on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T 4 S R 7 W
 S 16 | S 15
 S 21 | S 22
 1965

Deposit the original stone and iron pipe alongside
 the iron post.

S. 89° 36' W., bet. secs. 16 and 21.

Descend 15 ft. over gradual SW. slope, through heavy
 timber and dense undergrowth.

4.75 Creek, 5 lks. wide, course S. 70° W., from NE.; asc.
 55 ft. over SE. slope.

14.20 Top of ascent, slopes S. 20° W.; desc. 20 ft. over SW.
 slope.

BOOK 3

49