	Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.
17.60	Bottom of descent, slopes S.; asc. 5 ft. over SE. slope.
20.08	Point for the E 1/16 sec. cor. of secs. 16 and 21.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
,	In the ground, with blass cap mad.
	E $1/16 \frac{\text{S}}{\text{S}} \frac{16}{\text{S}}$ 1965
	from which
•	A fir, 13 ins. diam., bears N. 43½° W., 108 lks. dist., mkd. E1/16 S16 BT.
•	A fir, 8 ins. diam., bears S. 19° W., 30½ 1ks. dist., mkd. E1/16 S21 BT.
	Descend 30 ft. over SW. slope.
23.80	Bottom of descent, slopes S.; asc. 5 ft. over gradual SE. slope.
24.90	Top of ascent, slopes S.; desc. 40 ft. over SW. slope.
34.00	Bible Creek, 10 lks. wide, course S. 40° E.; asc. 35 ft. over E. slope.
35.00	Leave timber, edge bears N. and S., also wire fence, bears N. and S., enter open meadow.
36.70	Leave meadow, edge bears N. and S., also wire fence, bears N. and S., enter partially logged area.
36.90	Dirt road, 10 lks. wide, bears N. and S.
40.16	The \(\frac{1}{4}\) sec. cor. of secs. 16 and 21, perpetuated and recorded by Leo J. Martin, Registered Land Surveyor No.
	363, in 1965, with a galvanized iron pipe, $\frac{3}{4}$ in. diam., protruding 6 ins. above ground, firmly set alongside the
	original conglomerate stone, 14 x 12 x 8 ins., loosely set 2 ins. in the ground, with illegible marks visible on the top, from which bearing trees mkd. by Martin:
• 6	A fir, 43 ins. diam., bears N. 48° W., 97 lks. dist., mkd. 363 \(\frac{1}{4}\) S16 BT on open blaze.
	A fir, 20 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ W., 54 lks. dist., mkd. 363 $\frac{1}{4}$ S21 BT on open blaze.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
•	T 4 S R 7 W
)	$\frac{1}{4} \frac{S}{S} \frac{16}{21}$

Deposit the original stone and iron pipe alongside the iron post.

N. 89° 46° W., beginning new measurement.

Ascend 95 ft. over SE. slope.

BOOK 3