

## Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS	
8.20	Spur, slopes SE.; leave partially logged area, edge bears E. and SW.; desc. 50 ft. over SW. slope.
12.20	Ravine, drains S. $10^{\circ}$ W.; asc. 20 ft. over SE. slope, changing to S. slope.
15.00	Dirt road, 10 lks. wide, bears NW. and SE.
19.73	Point for the W 1/16 sec. cor. of secs. 16 and 21. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16   S 16 S 21 1965
	from which
	A fir, 20 ins. diam., bears N. $11^{\circ}$ W., $25\frac{1}{2}$ lks. dist., mkd. W1/16 S16 BT.
	A fir, 17 ins. diam., bears South, 7 lks. dist.; mkd. W1/16 S21 BT.
	Descend 60 ft. over SW. slope.
28.70	Creek, 2 lks. wide, course S. $35^{\circ}$ E.; asc. 15 ft. over SE. slope.
30.00	Top of ascent, slopes S.; desc. 195 ft. over steep SW. slope.
38.30	Bible Creek, 12 lks. wide, course NW.; desc. 10 ft. along rocky creek bottom.
39.46	The cor. of secs. 16, 17, 20, and 21.  Land, mountainous. Soil, clay and loam. Timber, fir, alder, willow, wild cherry, and maple; undergrowth, vine maple, salal, fern, huckleberry, and devil's club.
	North, bet. secs. 16 and 17.  Descend 1 ft. over rocky creek bed.
0.35	Bible Creek, 12 lks. wide, course N. $70^{\circ}$ W. from S. 50° E., asc. 275 ft. over steep SW. slope, through heavy timber and dense undergrowth.
7.50	Spur, slopes W.; desc. 155 ft. along W. slope, changing to NW. slope.
18.80	Spring branch, 1 lk. wide, course W.; asc. 30 ft. over SW. slope.
19.62	Point for the S 1/16 sec. cor. of secs. 16 and 17.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	S 1/16 S 17   S 16 1965

BOOK

3