

Township 1 South, Range 9 West

Chains

Latitude $45^{\circ} 27.9'$ N. Longitude $123^{\circ} 43.3'$ W.The mean magnetic declination is $20^{\circ} 58'$ E.

Dependent Resurvey of the Base Line, Portion of S. Bdy.
T. 1 N., R. 8 W.

(Mastering the 1856 survey by Samuel R. Snowden
and the 1884 Resurvey by Henry Meldrum)

Beginning at the corner of Sections 31 and 32 only, on the S. bdy. of T. 1 N., R. 8 W., determined from the original bearing trees, recovered and re-measured by the Oregon State Board of Forestry with an iron post, 1 $\frac{1}{2}$ ins. diam., protruding 3 ins. above ground, firmly set, in a mound of stones, 3 ft. base, to top, with 3 in. bronze cap and.

Oregon State Board of Forestry
T 1 N R 8 W
S L
S 31 & 32
1956
RS 359

from which the original bearing trees:

A hemlock snag, 36 ins. diam., bears N. $52\frac{1}{2}'$ E., 61 lks. dist., with scribe marks RSW T 18 S 5 visible on burned and opened double blaze.

A hemlock snag, 16 ins. diam., bears S. 72° E., 44 lks. dist., with scribe marks RSW T 18 S 5 visible on burned and opened double blaze. (Record bearing, S. $73\frac{1}{2}'$ E.; the marks on this tree were reported destroyed in the 1893 retracement by Frank H. Sharp).

A hemlock snag, 28 ins. diam., bears S. 16° W., 38 lks. dist., with scribe marks RSW T 18 S 5 visible on burned and opened double blaze. (Record bearing S. 22° W.; the marks on this tree were reported destroyed in the 1893 retracement by Frank H. Sharp).

A hemlock snag, 35 ins. diam., bears N. $20\frac{1}{2}'$ W., 35 lks. dist., with scribe marks RSW T 18 S 5 visible on burned and opened double blaze.

and trees marked by the Oregon State Board of Forestry in 1956:

An alder, 10 ins. diam., bears N. 30° E., 74 lks. dist., bark scribed T 1 N RSW S 32 BT.

A sawed fir stump, 56 ins. diam., bears N. 87° W., 23 lks. dist., with scribe marks T 1 N RSW S 31 BT RS 359 visible on unhealed blaze.

Add marks RSW 1959 to the bronze cap and mark a new bearing tree:

An alder, 7 ins. diam., bears N. 66° W., 36 lks. dist., bark scribed T 1 N RSW S 31 BT.

The corner falls at the N. side of a rotted log, 3 ft. diam.

S. $89^{\circ} 35'$ W., along the S. bdy. of Section 31, marking and blasing the true line.