

Dependent Resurvey of Base Line, Portion of S. Bdy. of T. 1 N., R. 9 W.

Chains 25.87	Branch, 1 lk. wide, course S. 10° W.; ascend 230 ft. over broken SE. slope.
32.50	End of skid road, bears N.; enter partially logged area.
33.66	Spur, slopes S.; descend 9 ft. along S. slope.
34.02	Point for the $\frac{1}{4}$ sec. cor. of Section 2 only, on the N. bdy. of T. 1 S., R. 9 W., hereinafter described.
	Descend 76 ft. over SW. slope.
37.265	Point for the $\frac{1}{4}$ sec. cor. of Section 33 only, restored by the method of broken boundaries; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mid.

T 1 N R 9 W
 $\frac{1}{4}$ S 33
1959

from which

A fir, 13 ins. diam., bears N. 66° E., 219 lks. dist.,
 mid. $\frac{1}{2}$ S 33 NW.

A fir, 23 ins. diam., bears N. 41° W., 109 lks. dist.,
 mid. $\frac{1}{2}$ S 33 NE.

Corner point falls at the end of a saved fir log, 36 ins. diam.

S. $89^{\circ} 42'$ W., beginning new measurement.

Descend 10 ft. along S. slope.

2.50	Ravine, drains S.; leave live old growth timber, edge bears NE. and SW.; ascend 260 ft. over SE. slope, through dead timber and dense reproduction.
3.50	Skid road, 10 lks. wide, bears N. 70° E. and S. 70° W.; leave logged area.
10.50	Junction of ridges, which bear NE., S., and NW.; descend 139 ft. over W. slope.
15.545	Point for the N 1/16 sec. cor. of Section 2 only, on the N. bdy. of T. 1 S., R. 9 W.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mid.

W 1/16 S 2
 1959

from which

A fir, 7 ins. diam., bears S. 39° E., 50 lks. dist.,
 mid. W 1/16 S 2 ET.

A hemlock, 5 ins. diam., bears S. $72\frac{1}{2}$ W., 30 lks. dist.,
 mid. W 1/16 S 2 ET.

Descend 620 ft. over steep W. slope.