

Dependent Resurvey of a Portion of the W. Bdy. of T. 1 S., R. 9 W.

Chains	A rotted hemlock stump and log, 13 ins. diam., bears S. 46° E., 36 lks. dist., with scribe mark B and other illegible scribe marks visible on partially healed and rotted blaze. (Record bearing, S. 37° E.)										
	and bearing trees reported destroyed in Neldrum's 1884 resurvey:										
	A spruce snag, 28 ins. diam., bears S. 13½° W., 16½ lks. dist., with no scribe marks visible on chopped out face.										
	A spruce snag, 37 ins. diam., bears N. 30° W., 43 lks. dist., with scribe marks T1S RSW visible on rotted face.										
	A spruce snag, 35 ins. diam., bears N. 10° W., 29 lks. dist., with no scribe marks visible on chopped out face.										
	At the corner point										
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap and.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 1 S</td> <td>T 1 S</td> </tr> <tr> <td>S 25</td> <td>S 19</td> </tr> <tr> <td>R 9 W</td> <td>S 30</td> </tr> <tr> <td></td> <td>R S W</td> </tr> <tr> <td colspan="2" style="text-align: center;">1958</td> </tr> </table>	T 1 S	T 1 S	S 25	S 19	R 9 W	S 30		R S W	1958	
T 1 S	T 1 S										
S 25	S 19										
R 9 W	S 30										
	R S W										
1958											
	from which new bearing trees:										
	A fir, 16 ins. diam., bears N. 66½° E., 43 lks. dist., and. T1S RSW S19 NE.										
	A fir, 29 ins. diam., bears S. 46° E., 28 lks. dist., and. T1S RSW S30 NE.										
	Deposit the basalt stone alongside the iron post.										
	The corner falls on a ridge bearing N. 30° E. and S. 30° W.										
	Land, mountainous. Soil, rocky clay. Timber, spruce, hemlock, fir, and alder; undergrowth, salmonberry, devil's-club, bucklerberry, vine maple, and reproduction.										
	N. 0° 33' W., along the W. bdy. of Section 19.										
	Descend 96 ft. along W. slope, changing to NW. slope, through heavy timber and dense undergrowth.										
6.43	Abandoned logging road at edge of timber, bears N. 50° E. and S. 50° W.; enter logged area.										
9.15	Abandoned logging road, bears NE. and SW.										
9.64	Spring branch, 1 lk. wide, course S. 70° W.; ascend 186 ft. over SW. slope.										
10.50	Same abandoned logging road, bears N. 60° W. and S. 60° E.										
16.67	Abandoned logging road at edge of logged area, bears N. 70° E. and S. 70° W.; enter timber.										
19.27	Spur ridge, bears N. 70° E. and S. 70° W.; descend 292 ft. over N. slope.										
23.91	The corner of Sections 24 and 25 only, on the E. bdy. of T. 1 S., R. 9 W., determined at record distance from each of the original bearing trees;										