

Dependent Resurvey of a Portion of the W. bdy. of T. 1 S., R. 8 W.

Chains 23.20	Leave timber and enter power line right of way, edge bears N. 65° E. and S. 65° W.
25.00	High voltage transmission line, bears N. 65° E. and S. 65° W.
27.00	Leave right of way and enter timber, edge bears N. 65° E. and S. 65° W.
29.04	Point for the $\frac{1}{4}$ sec. cor. of Section 13 only, on the E. bdy. of T. 1 S., R. 9 W., at midpoint latitudinally. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S S 13 R 9 W 1958
	from which
	A hemlock, 10 ins. diam., bears S. $5\frac{1}{2}^{\circ}$ W., 75 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S13 ET.
	A hemlock, 14 ins. diam., bears N. 66° W., 47 lks. dist., mkd. $\frac{1}{4}$ S13 ET.
	Ascend 34 ft. over SE. slope.
30.00	Spur, slopes E.; descend 182 ft. over NE. slope.
37.20	Branch, 3 lks. wide, course E.; ascend 5 ft. over S. slope.
37.33	Point for the corner of Sections 7 and 18 only, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S T 1 S R 9 W S 7 S 13 S 18 R 8 W 1958
	from which
	A spruce, 62 ins. diam., bears N. 74° E., 184 lks. dist., mkd. T18 RSW S7 ET.
	A hemlock, 42 ins. diam., bears S. 15° E., 76 lks. dist., mkd. T18 RSW S18 ET.
	Land, mountainous except for narrow Wilson River Valley. Soil, rocky clay with rock outcroppings and loam in the valley bottom. Timber, spruce, hemlock, alder, fir, cedar, and maple; undergrowth, salmonberry, devil's-club, huckleberry, young alder, and reproduction.
	N. 1° 19' E., along the W. bdy. of Section 7.
	Descend 10 ft. over NE. slope, through heavy timber and dense undergrowth.
1.10	Branch, 6 lks. wide, course SW.; ascend 253 ft. over SW. slope, changing to W. slope.
BOOK 3	10.04 Point for the N 1/16 sec. cor. of Section 13 only, on the E. bdy. of