

Dependent Resurvey of a Portion of the W. Bdy. of T. 1 S., R. 9 W.

	Chains	
0.25		Spur, slopes S. 80° W.; ascend 48 ft. along W. slope.
2.40		Top of ascent, slopes W.; descend 76 ft. over NW. slope.
4.70		Branch, 2 lks. wide, course W. curving to SW.; ascend 30 ft. over S. slope.
3.45		Point for the $\frac{1}{4}$ sec. cor. of Section 12 only, on the E. bdy. of T. 1 S., R. 9 W., hereinafter described.
		Ascend 175 ft. over steep S. slope.
8.00		Top of rock bluff, 30 ft. high, bears E. and W.; leave live old growth timber, edge bears NW. and SE.; ascend 133 ft. over S. slope, through old burned area covered with dense undergrowth.
10.15		The original line tree marked by Henry Meldrum in 1883, a solid fir snag, 48 ins. diam., with healed notches on N. and S. sides. This now becomes an angle point.
		N. $0^{\circ} 16'$ W., beginning new measurement.
		Ascend 12 ft. over S. slope.
0.57		Spur, slopes W.; descend 140 ft. over NW. slope.
4.90		Wet ravine, drains W.; ascend 70 ft. over steep SW. slope.
6.10		Spur, slopes W.; descend 35 ft. over NW. slope.
8.23		Point for the $\frac{3}{16}$ sec. cor. of Section 6 only.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		S 1/16 S 6 1939
		from which
		A fir, 40 ins. diam., bears N. 85° E., 90 lks. dist., mkd. S 1/16 S6 BT.
		A hemlock, 25 ins. diam., bears S. 32° E., $30\frac{1}{2}$ lks. dist., mkd. S 1/16 S6 BT.
		Descend 313 ft. over NW. slope.
10.855		Point for the $\frac{3}{16}$ sec. cor. of Section 12 only, at proportionate distance in latitude on the E. bdy. of T. 1 S., R. 9 W.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		N 1/16 S 12 1939
		from which
		A cedar, 70 ins. diam., bears S. 78° E., 13 lks. dist., mkd. X at breast height.
		A hemlock, 12 ins. diam., bears S. 42° W., $120\frac{1}{2}$ lks. dist., mkd. N 1/16 S12 BT.
		An alder, 6 ins. diam., bears N. 35° W., $47\frac{1}{2}$ lks. dist., bark scribed N 1/16 S12 BT.