Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains To establish the f sec. cor. of sec. 1 only, on the N. bdy. of the township, I return to the corner of Townships 1 North, Ranges 8 and 9 West, and wun

S. 67° 17' W., along the N. bdy. of sec. 1.

34.04 Point for the & sec. cor. of sec. 1 only, at proportionate distance in departure on the N. bdy. of sec. 1.

Set an iron post, 28 ins. long, 23 ins. diam., 24 ins. in the ground, with brass cap whd.

T 1 S R 9 W 1959

from which

- A spruce, 45 ins. dism., bears S. 77° E., 85 lks. dist., mkd. 2 81 BT.
- A fir, 30 ins. diam., bears S. 25° W., 106 lks. dist., mkd. 2 Sl BT.

To complete the survey of sec. 1, I return to the closing corner of secs. 1 and 12, on the E. bdy. of T. 1 S., R. 9 W., and run

M. 5º 13' W., along the E. bdy. of sec. 1.

42.55 Point for the 2 sec. cor. of sec. 1 only, on the E. bdy. of sec. 1, at proportionate distance.

Set am iron post, 28 ins. long, 25 ins. diam., 24 ins. in the ground, with brass cap skd.

T 1 S 1 R 9 W 1959

from which

- A hemlock, 17 ins. dism., bears 5. 69 W., 30 lks. dist., skd. & 81 BT.
- A hamlock, 32 ins. dism., bears N. 25° W., 21 lks. dist., mkd. 2 S1 B7.

From the cor. of secs. 14 and 23 on the W. bdy. of sec. 13.

8. 89° 53' W., bet. secs. 14 and 23.

Ascend 94 ft. over broken SE. slops, changing to S. slope, through scattering timber and dense undergrowth.

- 9.00 Revine, drains 5. 50° E.; asc. 463 ft. over steep, recky E. slope, changing to SE. slope.
- 19.12 Point for the E 1/16 sec. cor. of secs. 14 and 23.

Set on iron post, 26 ins. long, 23 ins. diam., 24 ins. in the ground, with bress cap akd.

E 1/16 \$ 14 5 23

from which

800K 3

134