

## Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

	Chains	A fir, 21 ins. diam., bears N. $65\frac{1}{2}$ ° E., 87 lks. dist., mkd. E 1/16 S14 BT.  A fir, 9 ins. diam., bears S. $45\frac{1}{2}$ ° W., 47 lks. dist., mkd. E 1/16 S23 BT.  Ascend 78 ft. along S. slope.
21.40		Ravine, course S. $70^{\circ}$ E.; asc. 256 ft. over steep, rocky E. slope.
26.10		Spur, slopes S. $30^{\circ}$ E.; desc. 11 ft. along S. slope.
29.75		Head of ravine, drains S.; asc. 56 ft. along S. slope.
33.80		Spur ridge, bears N. $75^{\circ}$ E. and S. $75^{\circ}$ W.; desc. 141 ft. over NW. slope.
37.00		Leave old burned area, edge bears NE. and SW.; enter heavy old growth timber.
38.24		Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T 1 S R 9 W $\frac{1}{4} \frac{S 14}{S 23}$ 1958
		from which
		A hemlock, 35 ins. diam., bears N. $64^{\circ}$ W., $32\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S14 BT.
		A hemlock, 25 ins. diam., bears S. $33\frac{1}{2}$ ° W., $69\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S23 BT.
		The corner falls N. of a spruce snag.
		Descend 329 ft. over NW. slope, changing to steep W. slope.
47.00		Leave old growth timber, edge bears NE. and SW.; enter old burned area.
49.20		Ravine, drains SW.; desc. 189 ft. along broken S. slope.
57.36		Point for the W 1/16 sec. cor. of secs. 14 and 23.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		W 1/16 $\frac{S 14}{S 23}$ 1958
		from which
		A hemlock, 11 ins. diam., bears N. $32^{\circ}$ W., 12 lks. dist., mkd. W 1/16 S14 BT.
		A fir, 11 ins. diam., bears S. $62\frac{1}{2}$ ° W., 10 lks. dist., mkd. W 1/16 S23 BT.
		Descend 258 ft. over SW. slope.
65.60		Spring seepage, drains W.; desc. 60 ft. over W. slope of rock outcropping.