

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	A rotted spruce stump, 50 ins. diam., bears N. 73° W., 100 lks. dist., with no marks remaining. (Record distance, 110 lks.)
	At the corner point Cement a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$ ins. stem, in a drill hole, with top mkd.
	T 1 S R 9 W S 15 S 14 ---+--- S 22 1958
	from which new bearing trees: A hemlock, 16 ins. diam., bears S. $40\frac{1}{2}^{\circ}$ W., 161 lks. dist., mkd. T1S R9W S22 BT. A hemlock, 30 ins. diam., bears N. 54° W., 91 lks. dist., mkd. T1S R9W S15 BT. The corner is located at the S. edge of creek, 3 lks. wide, course W.
	N. $1^{\circ} 06'$ E., beginning new measurement. Ascend 257 ft. over S. slope.
5.40	Spur, slopes S. 30° W.; asc. 11 ft. along gradual W. slope.
11.00	Leave timber, edge bears N. 10° E. and W.; enter logged area.
17.17	Point for the S 1/16 sec. cor. of sec. 14 only, on the W. bdy. of sec. 14. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 14 ---+--- 1958
	from which A sawed spruce stump, 96 ins. diam., bears N. 44° E., 34 lks. dist., mkd. S 1/16 S14 BT. A spruce, 70 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ E., 180 lks. dist., mkd. S 1/16 S14 BT.
	Ascend 14 ft. over SW. slope.
18.00	Spur, slopes W.; desc. 274 ft. over steep N. slope.
21.10	Leave logged area, edge bears S. 10° E. and W.; enter heavy timber and dense undergrowth.
24.54	Branch, 4 lks. wide, course N. 80° W.; asc. 50 ft. over S. slope.
26.30	Top of ascent, slopes W.; desc. 38 ft. over NW. slope.
28.90	Branch, 4 lks. wide, course S. 70° W.; asc. 117 ft. over S. slope.
34.20	Slope becomes steep; asc. 120 ft. over steep S. slope.
36.40	Point for the $\frac{1}{4}$ sec. cor. of sec. 14 only, at midpoint latitudinally on the W. bdy. of sec. 14.