

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	T 1 S R 9 W S 10 S 11 S 15 1958
	from which
	A fir, 25 ins. diam., bears S. 70° W., 48 lks. dist., mkd. T1S R9W S15 BT.
	A fir, 28 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ W., 61 $\frac{1}{2}$ lks. dist., mkd. T1S R9W S10 BT.
	N. $6^{\circ} 41'$ W., beginning new measurement.
	Ascend 187 ft. over S. slope.
7.60	Main ridge dividing Kilchis River and Wilson River drainage, bears NE. and SW.; desc. 135 ft. over NW. slope, changing to W. slope, through heavy timber and light undergrowth.
18.60	Spur, slopes N. 20° W.; desc. 400 ft. over steep NE. slope.
24.80	Branch, 1 lk. wide, course N. 50° W.; desc. 108 ft. along W. slope, changing to N. slope.
31.50	Branch, 4 lks. wide, course W.; asc. 240 ft. over S. slope.
38.81	The $\frac{1}{2}$ sec. cor. of secs. 10 and 11, determined at record distance from each of the original bearing trees:
	A fir, 71 ins. diam., bears N. 58° E., 25 lks. dist., with scribe marks BT visible on partially opened blaze. (Record, N. 48° E.)
	A fir, 23 ins. diam., bears N. $15\frac{1}{2}^{\circ}$ W., 16 lks. dist., with no scribe marks visible on opened blaze. (Record, N. $20\frac{1}{2}^{\circ}$ W.)
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 9 W S 10 S 11 S 15 1958
	from which new bearing trees:
	A fir, 40 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ E., 128 lks. dist., mkd. $\frac{1}{2}$ S11 BT.
	A fir, 26 ins. diam., bears N. 56° W., 25 lks. dist., mkd. $\frac{1}{2}$ S10 BT.
	N. $0^{\circ} 56'$ E., beginning new measurement.
	Ascend 170 ft. over S. slope.
4.20	Spur, slopes S. 50° W.; asc. 120 ft. along broken W. slope.
14.70	Spur, slopes W.; desc. 65 ft. over NW. slope.