

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains 18.32	<p>Point for the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set on iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone, 2 ft. base, to top, with brass cap mid.</p> <p style="text-align: center;">N 1/16 S 10 S 11 1958</p> <p>from which</p> <p>A hemlock, 26 ins. diam., bears S. $54\frac{1}{2}$° E., 44 lks. dist., mid. N 1/16 S11 BT.</p> <p>A fir, 14 ins. diam., bears S. $82\frac{1}{2}$° W., 29 lks. dist., mid. N 1/16 S10 BT.</p> <p>Descend 140 ft. over NW. slope.</p>
20.60	Spring seepage, drains NW.; asc. 68 ft. along W. slope.
27.00	Spur, slopes N. 80° W.; desc. 367 ft. over steep N. slope.
33.40	Leave timber, edge bears E. and W.; enter old logged area covered with dense undergrowth.
36.64	The cor. of secs. 2, 3, 10, and 11, determined from the remaining original bearing trees, recorded and recommended by the Oregon State Board of Forestry with an iron post, 1½ ins. diam., protruding 6 ins. above ground, firmly set, with 3 in. bronze cap mid.
	Oregon State Board of Forestry T 1 S R 9 W S 3 S 2 S 10 S 11 1958 RS 401
	from which the remaining original bearing trees:
	A hemlock snag, 28 ins. diam., bears S. 15° E., 16 lks. dist., (25 lks. slope distance) with scribe marks S R9 11 visible on partially opened blaze. (Record, S. $9\frac{1}{2}$ ° E., 25 lks. dist.)
	A sawed hemlock stump, 29 ins. diam., bears S. 75° W., $72\frac{1}{2}$ lks. dist. (83 lks. slope distance), with scribe marks S visible on partially opened blaze. (Record, S. $70\frac{1}{2}$ ° W., 83 lks. dist.)
	A sawed hemlock stump, 40 ins. diam., bears N. $59\frac{1}{2}$ ° W., 79 lks. dist. (level), with scribe mark S visible on partially opened blaze.
	and trees marked by the Oregon State Board of Forestry in 1957:
	An alder, 5 ins. diam., bears N. 46° E., 19 lks. dist., bark scribed T1S R9W S2 BT.
	An alder, 12 ins. diam., bears S. 55° E., 44 lks. dist., bark scribed T1S R9W S11 BT RS401.
	An alder, 5 ins. diam., bears S. 67° W., 24 lks. dist., bark scribed T1S R9W S10 BT.
	A hemlock, 30 ins. diam., bears N. 32° W., 159 lks. dist., with scribe marks T1S R9W S3 BT visible on unhealed blaze.