

## Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	An alder, 8 ins. diam., bears N. 13° W., 77 lbs. dist., bark scribed $\frac{1}{4}$ S2 BT.  An alder, 6 ins. diam., bears S. 10° W., 44½ lbs. dist., bark scribed $\frac{1}{4}$ S11 BT.  The corner falls on S. shoulder of skid road bearing W.  Ascend 78 ft. along S. slope, along S. edge of logged area, through scattering timber and dense undergrowth.
50.00	Ridge, bears N. 75° E. and S. 65° W.; desc. 900 ft. over steep, broken, rocky NW. slope.
74.50	Waterfall in wet ravine, 30 ft. high, drains N. 30° W.; asc. 26 ft. along steep W. slope.
75.46	The cor. of secs. 2, 3, 10, and 11.  Land, mountainous with rock outcroppings. Soil, rocky clay. Timber, hemlock, fir, spruce, alder, and cedar; undergrowth, salmonberry, vine maple, huckleberry, devil's-club, young alder and reproduction.
	N. 0° 27' W., bet. secs. 2 and 3.  Descend 60 ft. over NE. slope, through old logged area covered with dense undergrowth.
2.30	Branch, 2 lbs. wide, course NW.; desc. 13 ft. along W. slope.
3.20	Branch, 4 lbs. wide, course W.; asc. 376 ft. over SW. slope.
11.84	Spur, slopes W.; desc. 190 ft. over NW. slope.
16.36	Ravine, drains W.; ascend 75 ft. over rocky SW. slope.
19.30	Spur, slopes W.; desc. 178 ft. over NW. slope.
23.00	Branch, 1 lk. wide, course N. 60° W.; desc. 155 ft. along W. slope, changing to NW. slope.
30.30	Branch, 5 lbs. wide, course S. 60° W.; asc. 506 ft. over steep, rocky S. slope, changing to SE. slope.
31.70	Gravelled logging road, 15 lbs. wide, bears N. 60° E. and S. 70° W.
33.00	Leave logged area, edge bears E. and W.; enter heavy timber and light undergrowth.
42.80	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	 from which  A fir, 25 ins. diam., bears N. 65° E., 73 lbs. dist., mkd. $\frac{1}{4}$ S2 BT.