

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	A fir, 18 ins. diam., bears S. 62° W., 26 lks. dist., mkd. $\frac{1}{4}$ S3 BT. Ascend 156 ft. over SE. slope, changing to S. slope.
43.00	Spur, slopes SW.; desc. 400 ft. along W. slope, changing to NW. slope.
62.46	Branch, 3 lks. wide, course W.; asc. 74 ft. over S. slope.
64.20	Point for the N 1/16 sec. cor. of secs. 2 and 3. Set an iron post, 28 ins. long, $2\frac{1}{4}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 3 S 2 1959
	from which
	A hemlock, 32 ins. diam., bears S. 56° E., 36 lks. dist., mkd. N 1/16 S2 BT.
	A hemlock, 21 ins. diam., bears N. 56° W., 56 lks. dist., mkd. N 1/16 S3 BT.
	Descend 75 ft. over NW. slope.
64.50	Leave timber, edge bears E. and W.; enter open logged area.
68.40	Branch, 3 lks. wide, course W.; asc. 190 ft. over SW. slope, changing to W. slope.
76.70	Top of ascent, slopes W.; desc. 50 ft. over NW. slope.
79.80	Branch, 2 lks. wide, course SW.; asc. 295 ft. over S. slope.
85.81	Intersect the Base Line. Point for the closing corner of secs. 2 and 3, at proportionate distance in departure; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{4}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 N R 9 W S 35 S 3 S 2 T 1 S R 9 W C C 1959
	from which
	A sawed hemlock stump, 60 ins. diam., bears S. 50° E., 80 lks. dist., mkd. T1S R9W S2 CC BT.
	A sawed fir stump, 55 ins. diam., bears S. 52° W., 102 lks. dist., mkd. T1S R9W S3 CC BT.
	The corner falls at the W. side of a sawed fir stump, 84 ins. diam.
	From this point the cor. of secs. 34 and 35 only, on the S. bdy. of T. 1 N., R. 9 W., bears S. $89^{\circ} 42'$ W., 2.34 chs. dist., previously described.