Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

Land, mountainous.
Soil, rocky clay with rock outcroppings.
Timber, hemlock, fir, spruce, and alder; undergrowth, sword fern, davil's-club, vine maple, huckleberry, salmonberry, young alder, and reproduction.

To complete the survey of sec. 2, I return to the \(\frac{1}{2}\) sec. cor. of sec. 35 only, on the S. bdy. of sec. 35, T. l N., R. 9 W., and run

N. 87° 17' E., slong the N. bdy. of sec. 2.

3.245

Point for the & sec. cor. of sec. 2 only, at midpoint in departure on the N. bdy. of sec. 2.

Set on iron post, 28 ins. long, 24 ins. diam., 24 ins. in the ground, with brass cap mkd.

from which

- A hemlock, 28 ins. diam., bears S. 264° E., 212 lks. dist., mkd. 2 82 BT.
- A fir, 13 ins. dism., beers S. $12\frac{1}{2}$ ° W., 130 lks. dist., mkd. $\frac{1}{6}$ S2 BT.

From the & sec. cor. of secs. 15 and 16, determined at record bearing and distance from the remaining bearing tree established by the County Surveyor about 80 years ago in a perpetuation of the original corner.

from which the remaining County Surveyor bearing tree;

An alder, 37 ins. dism., bears N. 72° E., 87 lks. dist., bark scribed & S CS.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brase cap wkd.

from which

- A hemlock, 8 ins. diem., beers N. 591° E., 183 lks. dist., mkd. 2 815 BT.
- A spruce, 38 ins. dism., besrs S. 26° W., 94 lks. dist., mkd. 4 S16 BT.

From this point a locally established cor., bears N. 9° W., 190 lks. dist., monumented with a drive shaft housing, 2 ins. dism., protruding 2 ft. above ground, firmly set, alongside the cor. of feaces bearing N. 10° E., S. 10° W., and H. 80° W.

N. 0° 10° W., bet. secs. 15 and 16.

Ascend 345 ft. over S. slope, through scattering timber and dense undergrowth.

BOOK 9 4

12/6