

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

- Chaining
- 26.50 Branch, 2 lks. wide, course NE.; desc. 120 ft. along E. slope, changing to NE. slope.
- 33.10 Creek, 3 lks. wide, course N. 80° E.; asc. 20 ft. over SE. slope, changing to E. slope.
- 38.37 The $\frac{1}{2}$ sec. cor. of secs. 3 and 4, determined from the original bearing trees:
- A fir, 21 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., 130 lks. dist., (157 lks. slope distance), with scribe marks $\frac{1}{2}$ visible on partially opened blaze. (Record, S. 10° E., 157 lks. dist.)
- A fir, 40 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ W., 31 lks. dist., (40 lks. slope distance), mkd. with a healed double blaze. (Record distance, 40 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which a new bearing tree:

A fir, 15 ins. diam., bears East, 20 lks. dist., mkd. $\frac{1}{2}$ SS BT.

N. $3^{\circ} 23'$ W., beginning new measurement.

Ascend 115 ft. over SE. slope.

- 6.10 Spur, slopes N. 70° E.; desc. 750 ft. over broken NW. slope, changing to N. slope.
- 33.00 Clear Creek, 15 lks. wide, course NW., curving to N.; asc. 135 ft. along broken W. slope, changing to SW. slope.
- 48.00 Spur, slopes W.; desc. 10 ft. over NW. slope.

Intersect the Base Line.

Point for the closing cor. of secs. 3 and 4, at proportionate distance in departure; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 45 ins. diam., bears S. 76° E., 71 lks. dist., mkd. TIS NW 83 CC BT.