## Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

Set an iron post, 28 ins. long, 25 ins. diam., 24 ins. in the ground, with brass cap mkd.

## from which

An alder, 4 ins. diam., bears N. 80° E., 44½ lks. dist., bark scribed & 85 BT.

A sawed spruce stump, 70 ins. diam., bears S. 38° W., 73 lks. dist., mkd. & 86 BT.

The corner falls on an abandoned log landing.

Ascend 10 ft. along gradual W. slope.

50.20 Branch, 2 lks. wide, course W.; asc. 157 ft. over SW. slope, changing to W. slope.

58.90 Leave logged area, edges bear N. and E.; enter timber.

64.00 Wet ravine, drains W.; asc. 100 ft. over S. slope, changing to SW. slope.

68.50 Top of ascent, slopes W.; desc. 280 ft. over NW. slope, changing to N. slope.

79.00 Old wire fence along edge of Kilchis River Valley bottom, bears E. and W.

79.56 The cor. of secs. 5, 6, 31, and 32, on the Base Line, previously described.

Land, foothills along the E. side of the Kilchis River valley. Soil, clay and loam.
Timber, hemlock, spruce, alder, and maple; undergrowth, wild blackberry, salmonberry, huckleberry, thimbleberry, vina maple,

To complete the survey of sec. 5, I return to the t sec. cor. of sec. 32 only, on the S. bdy. of sec. 32, T. 1 N., R. 9 W., and run

8. 89° 11' E., along the N. bdy. of sec. 5.

young alders, and reproduction.

0.445 Point for the t sec. cor. of sec. 5 only, at midpoint on the N. bdy. of sec. 5.

Set an iron post, 28 ins. long, 22 ins. diam., 24 ins. in the ground, with brass cap mkd.

## from which

A hemlock, 15 ins. diam., bears S. 35° E., 69 lks. dist., mkd. 2 85 BT.

A spruce, 13 ins. diam., bears S.  $82^{\circ}$  W.,  $69\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S5 BT.