

Resurvey of Portion of North Boundary of
T. 3 S., R. 10 W.

Chains.	S. $89^{\circ}42'W.$, on true line on S. bdy. of sec. 34.
	Asc. 50 ft. over gradual, broken NE. slope, through heavy timber and dense undergrowth.
7.30	Creek, 2 lks. wide, course NW.
10.30	Desc. 25 ft. over gradual NW. slope.
14.70	Creek, 2 lks. wide, course NW., asc. 218 ft. over E. slope.
23.10	Spur, slopes S., desc. 41 ft. over W. slope.
30.98	True point for closing cor. of secs. 3 and 4, as herein-after determined.
32.10	Small saddle on top of ridge, bears N. and S., asc. 115 ft. over E. slope.
39.91	Cor. of secs. 33 and 34 only, which is a piece of stake, very rotten, from which
	Old snag, 26 ins. diam., bears N. 46° E., 46 lks. dist., mkd. S 33 B T. (Old B. T.)
	A hemlock, 36 ins. diam., bears S. 27° W., (not S. 4° E.) 17 lks. dist., marks grown over. (Old B. T.)
	A hemlock, 14 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ W., (not N. 64° W., 35 lks.) 37 lks. dist., mkd. S 33 B T. (Old B. T.)
	At point for cor.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 33 and 34 only, with brass cap mkd.
	T2S R10W S33 S34
	T3S R10W S4 1933
	from which
	A hemlock, 14 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ W., 37 lks. dist., mkd. T 2 S R 10 W S 33 B T. (Old B. T. remarked)
	A hemlock, 25 ins. diam., bears N. 1° E., 51 lks. dist., mkd. T 2 S R 10 W S 34 B T. (New B. T.)
	Land, mountainous. Soil, sandy loam, 2nd rate. Timber, hemlock, spruce, cedar, and alder. Undergrowth, vine maple, salal, alder, fern, Devil's club, and wild blackberry.

"Reestablishment of the survey executed by Albert P. Wilson, U. S. Deputy Surveyor, in 1890."

Retracement.

From the cor. of Tps. 2 S., Rs. 10 and 11 W. 1933