

Resurvey of Portion of North Boundary of

T. 3 S., R. 10 W.

Chains

A hemlock, 14 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ E., 35 lks.
dist., mkd. T 2 S R 10 W S 31 B T. (New B. T.)

A hemlock, 30 ins. diam., bears N. 32° W., (not
N. 42° W.) 56 lks. dist., marks grown over. (Old
B. T.)

Land, mountainous.

Soil, sandy loam, 3rd rate.

Timber, hemlock, spruce, cedar, and alder.

Undergrowth, vine maple, salal, alder, fern, Devil's club,
and wild blackberry.

Dependent Resurvey of Portion of West Boundary of

T. 3 S., R. 10 W.

"Reestablishment of the survey executed by Albert P.
Wilson, U. S. Deputy Surveyor, in 1890."

Retracement

From the cor. of secs. 1, 6, 7, and 12, on W. bdy. of Tp.
North, retracing bet. secs. 1 and 6.

Find, no trace of S1/16 sec. cor. of secs. 1 and 6.

Find no trace of $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

True Line.

Point for the cor. of secs. 1, 6, 7, and 12, determined
by record bearing and distances to original bearing
trees.

at point for cor. of secs. 1 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 1, 6, 7, and 12, with
brass cap mkd.

R11W	R10W
S 1	S 6

Subdivided to points S12 | S 7

on Oct. 1, 1933.

from which

A spruce, 34 ins. diam., bears N. 31° E., 81 lks.
dist., marks grown over. (Old B. T.)

A spruce, 40 ins. diam., bears S. 82° E., 60 lks.
dist., marks grown over. (Old B. T.)

A spruce, 44 ins. diam., bears S. 60° W., 47 lks.
dist., marks grown over. (Old B. T.)

A snag, 30 ins. diam., bears N. 50° W., 50 lks.
dist., mkd. T 3 S R 11 W S 1 B T. (Old B. T.)

BOOK 3 A spruce, 36 ins. diam., bears N. 60° W., 72 lks.
dist., mkd. T 3 S R 11 W S 1 B T. (New B. T.)

Thence 198