

Dependent Resurvey of Portion of Subdivisional Lines of 137

T. 3 S., R. 10 W.

Chains.

T3S	R10W
S 6	S 5
<hr/>	
S 7	S 8

1933

from which

A hemlock, dead, 12 ins. diam., bears N. 42° E., 36 lks. dist., mkd. S 5 B T. (Old B. T.)

A hemlock, 20 ins. diam., bears S. 79° E., (not S. 70° E., 45 lks. dist., marks grown over. (Old B. T.)

A hemlock, 12 ins. diam., bears S. 72° W., 11 lks. dist., marks grown over. (Old B. T.)

A hemlock, 20 ins. diam., bears N. 42° W., 43 lks. dist., mkd. T 3 S R 10 W S 6 B T. (New B. T.)

A hemlock, 16 ins. diam., bears N. 66° E., 79 lks. dist., mkd. T 3 S R 10 W S 5 B T. (New B. T.)

Land, mountainous.

Soil, sandy loam, 3rd rate.

Timber, hemlock, fir, spruce, cedar, and alder.

Undergrowth, vine maple, salal, fern, alder, Devil's club, and wild blackberry.

From the cor. of secs. 5, 6, 7, and 8. S. $87^{\circ}39'W.$, on true line bet. secs. 6 and 7.

Asc. 14 ft. over SE. slope, through heavy timber and dense undergrowth.

0.90 Spur, slopes S., over rolling land.

3.20 Draw, course S.

7.48 Desc. 107 ft. over SW. slope.

10.60 Creek, 3 lks. wide, course S., over small spur, slopes S.

12.90 Creek, 2 lks. wide, course SE., asc. 133 ft. over SE. slope.

17.88 Spur, slopes S., desc. 190 ft. over SW. slope.

29.00 Creek, 3 lks. wide, course SW., asc. 15 ft. over SE. slope.

34.00 Spur, slopes S., desc. 74 ft. over SW. slope.

36.47 Creek, 2 lks. wide, course S., over rolling land.

39.46 Point for $\frac{1}{4}$ sec. cor. of secs. 6 and 7, as determined by reference to record bearing and distance from the SE., and record distance from the NE. original bearing trees.

At point for $\frac{1}{4}$ sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.