

Survey of Portion of Subdivisional Lines of

T. 3 S., R. 10 W.

Chains.

brass cap mkd.

T2S R10W

S33

S 5 | S 4

T3S R10W

C | C

1933

from which

A hemlock, 20 ins. diam., bears S. 54° E., 54 lks dist., mkd. T 3 S R 10 W S 4 C C B T.

A cedar, 48 ins. diam., bears S. 68° W., 121 lks. dist., mkd. T 3 S R 10 W S 5 C C B T.

From this point the cor. of secs. 32 and 33 only, T. R. 10 W., heretofore described, bears S. 89° 03' W., 13.66 chs. dist.

Land, mountainous. Soil, sandy loam, 3rd rate. Timber, hemlock, cedar, spruce, and alder. Undergrowth, vinemaple, salal, fern, alder, Devil's c. and wild blackberry.

From the cor. of secs. 5, 6, 7, and 8,

N. 0° 02' W., on true line bet. secs. 5 and 6.

Asc. 199 ft. over S. slope, through heavy timber and dense undergrowth.

7.51 Ravine, course SW., asc. 121 ft. over SW. slope.

13.75 Ridge, bears E. and W., desc. 46 ft. over N. slope.

18.05 Creek, 3 lks. wide, course W., over rolling land.

20.30 Creek, 3 lks. wide, course S. 15° W., asc. 809 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S 6 | S 5

1933

from which

A hemlock, 24 ins. diam., bears N. 27 1/2° E., 25 lks dist., mkd. 1/2 S 5 B T.

A hemlock, 18 ins. diam., bears S. 45° W., 14 lks. dist., mkd. 1/2 S 6 B T.

51.00 Ridge, bears E. and W., desc. 479 ft. over N. slope.

70.15 Creek, 4 lks. wide, course W., asc. 133 ft. over SW. slope.

77.50 Spur, slopes W., desc. 30 ft. over N. slope.

79.87 Intersect S. bdy. of sec. 32, T. 2 S., R. 10 W.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in